

Agenda Files Output to file Input from file

Files
Introduction to VBA programming - (c) 2009 Dario Bonino

1







2

Closing a file

- To close a file
 - The file numeric identifier is needed
 Close #fileid1
 - Multiple files can be closed at the same time
 Close #fileid1, #fileid2, #fileid3
 - To close all files
 - Close
 - Introduction to VBA programming (c) 2009 Dario Bonino



Writing to file

```
    Print allows to print some expressions to a file
    Print #fileid, expression1;
expression2; expression3
    #fileid - identifies the file to which expressions must
be output
    expression - what to print in the file
    Strings
    Result of numerical expressions
    ...
    Print #3, "The result is: "; result
Introduction to VBA programming - (c) 2009 Dario Bonino
```

Example 1

```
Open "results.txt" For Output As #4
Print #4, "#results"
Print #4,"|x|y|"
For i=0 To 10
    Print #4, "|";x(i);"|";y(i);"|"
Next I
Close #4
```

Introduction to VBA programming - (c) 2009 Dario Bonino

Exercise 1

Write a program that given a number N computes all the powers of 2 from 0 to N
 2⁰=1, 2¹=2,..... 2^N=?

- The computed values must be saved on a file named powers.txt with a tab separated format
 0 1
 - **1**2
 - **2** 2 4
 - **3**8



Reading from files

- $\hfill\square$ To read one or more values from a file
 - Input #fileid, variable1, variable2
 #fileid
 - The numeric identifier of the file to be read
 - □variable1…n
 - The variable in which to store the values read from the file
 - The filling behavior changes depending on the variable type
 - Introduction to VBA programming (c) 2009 Dario Bonino

Reading from files

- If the variable to be read is a string, the input function
 - skips any initial white space (spaces and TABs);
 - reads all the characters until a string field separator (commas and new-line characters) is found;
 - assigns them to variable.

Introduction to VBA programming - (c) 2009 Dario Bonino

Reading from files

If the variable to be read is numeric, the input function
 skips any initial white space (spaces and TABs);

- reads all the contiguous characters
- passes them to the Val function in order to have a numerical value (if a reading returns a non-number or an empty string, value 0 is produced);
- reads all characters until a number field separator (commas, new-line characters, spaces, and TABs) is found (after a field, white space before a comma or new-line is ignored);
- assigns the resulting value to the variable.

Example
 Suppose we want to read one two, three , four five Six, seven , eight nine, ten We write the following statements
<pre>Input #1, A Input #1, B Input #1, C Input #1, C Input #1, E Input #1, F Input #1, F Input #1, G</pre>
Introduction to VBA programming - (c) 2009 Dario Bonino

Example (cont.d)

What we expect to be the value of ABCDEFG?

■ A = "one two"

■ B = "three"

 \Box C = "four five"

D = "Six"

E = "seven"

■ F = "eight nine"

□ G = "ten"

Introduction to VBA programming - (c) 2009 Dario Bonino

Example2

🗆 August 16, 2006 Wednesday		
Dim A As String		
Dim B As Integer		
Dim C As String		
Input #1, A, B, C		
□ A = "August 16"		
□ B = 2006		
🗆 C = Wednesday		

Example3

Characters enclosed in quotes are read as single strings
 "Hello Everybody"
 Input #1, A

□A = "Hello Everybody"

Introduction to VBA programming - (c) 2009 Dario Bonino

Utilities

 The write function works as the print function but already encloses string between double quotes and writes the correct field separator characters
 Write #1, variable1, variable2,..., variableN

 To read one entire line inside a variable the Line Input instruction can be used
 Line Input #1, theWholeLine

Introduction to VBA programming - (c) 2009 Dario Bonino

End of File?

□ We can read from files but...

- How can we detect the file end?
- The EOF (End Of File) function allows to check if a file still contains something to read
 - □ True the end of the file has been reached
 - False the file has some more data to read
 - EOF(#fileId)
 - Usually we cannot assume to know the number of fields to be read in a file....

Example

 Read a file line by line and show the line content until the file is finished
 Open "input.txt" For Input As #1
 Do While Not EOF(1)
 Line Input #1, line
 MsgBox (line)
 Loop

Introduction to VBA programming - (c) 2009 Dario Bonino

Example 2

Use a text editor and create a file with some numbers, one on each line. Now write a program that asks the user for the name of the file to read, then calculates and displays how many values there are in that file, their maximum and minimum value, their sum and average.

Introduction to VBA programming - (c) 2009 Dario Bonino

Exercise 2

- Write a program that reads all the lines of a file, and writes them in reverse order (i.e. printing the line content from right to left) in another file.
- Display a MsgBox reporting how many rows have been copied.

Exercise 3

Write a program to encrypt and decrypt a text file by using Julius Caesar's cipher method. The program asks the user for the input file, the output file and a secret key (a whole number). Encryption is achieved by substituting uppercase and lowercase letters with other letters based on the key. Each letter position is shifted by key positions: for example, suppose key=3, then "A" becomes "D", "B" becomes "E", etc. and "X" becomes "A", "Y" becomes "B", and "Z" becomes "C". The same for lowercase letters. To decrypt an encrypted text, a negative value for key (e.g. -3) is used.

 A
 B
 C
 D
 E
 F
 G
 H
 I
 J
 K
 L
 M
 N
 O
 P
 Q
 R
 S
 T
 U
 V
 W
 X
 Y
 Z

 D
 E
 F
 G
 H
 I
 J
 K
 L
 M
 N
 O
 P
 Q
 R
 S
 T
 U
 V
 W
 X
 Y
 Z
 A
 B
 C

Exercise 4

- □ Write a program that reads a matrix from a file
 - The file reports the values of the matrix cells on separated rows, one per each matrix row
 - Values inside a row are separated by a space
 - The first line of the file contains 2 values respectively reporting the number of rows and columns of the matrix





Exercise 5

- Write a program that given a matrix M computes the smoothed matrix MS using the following algorithm
 - The MS(i,j) value is provided by the average of the values of the cells surrounding the same position in M ■ MS(i, j) = (M(i-1, j-1)+ M(i-1, j)+ M(i-1, j+1)+ M(i,j-1)+ M(i, j)+ M(i,j+1)+ M(i+1,j-1)+ M(i+1,j)+ M(i+1,j+1)) / 9
 - The initial matrix must be read from a file having the format defined in Exercise 4
 - The smoothed matrix must be saved in a file having the same format